



Remember to allow for the protrusion of the cylinder for the lever handle back plate – 12.5mm, or escutcheons – 7mm or 9mm. Specify door thickness when ordering this product. Refer chant™ Escutcheons in Accessories Section for thickness.

Note: The Cylinder Escutcheon on this side is concentric with the cylinder body. The Turn Escutcheon on the opposite side is above the Cylinder Escutcheon and is concentric with the cylinder barrel. Hole preparation for the cylinder through the door must be made accordingly.



## Profile Cylinder Turn Adaptors

All profile cylinder locks can use a chant Profile Cylinder Turn Adaptor with chant door handles and escutcheons. Cylinder plates can be used on the outside of the door with the adaptor bar connecting to the recess in the back of the thumb turn on the inside plate, or standard turn escutcheon.

Ensure the cylinder is the correct length when considering use with escutcheons and lever plate furniture.

These codes have a 8mm square adapter

1241	- 5 pin	31mm to door centreline
1242	- 6 pin	35mm to door centreline
1243	- 5 pin	38mm to door centreline
1243a	- 5 pin	40mm to door centreline
1244	- 5 pin	45mm to door centreline
1245	- 6 pin	50mm to door centreline

## Baton Cylinder Turn Adaptors

Schlage Key Profile

1241 -1	- 5 pin	31mm to door centreline
1242 -1	- 5 pin	36mm to door centreline
1243 -1	- 5 pin	41mm to door centreline
1245 -1	- 5 pin	51mm to door centreline

## Cam Adaptors

Designed to fit into Chant and other Profile Cylinder Locks, to suit various thumb turn spindle bars rotating 360°.

Code No.	Spindle Size
1250 - 16	6mm x 2mm
1251 - 16	5mm square
1252 - 16	6mm square
1253 - 16	8mm square
1250 - 18	6mm x 2mm
1251 - 18	5mm square
1252 - 18	6mm square
1253 - 18	8mm square
1254 - 20	8mm x 20mm Assa Abloy Optimal Pinnacle locks